

SUPERDOME DRUM



BENT MANUFACTURING COMPANY

SUPERDOME DRUM and BASE

FEATURES:

- Double (one on each side) flag mount holes with pre-molded stops for all-purpose flagging situations.
- Enlarged arch carry handle allows gloved workers easy, comfortable and secure grip.
- Ribbed dome top for increased target value and superior structural strength.
- High gravity molded rubber base hugs the road as if it were “glued down.”
- Recessed reflective band tiers, maximum width 6". Accommodates USA M.U.T.C.D. 2" maximum spacing specifications.
- Two pre-molded light mounts are designed for standard size bolt and cup washers.
- Rounded dome top discourages any dangerous debris or rocks to collect on top of drum.
- Tested and certified to meet the crashworthy requirements of NCHRP-350.



SPECIFICATIONS:

Drum Materials	Low or high density polyethylene
Color	Cad. orange
Drum Weight	LDPE (12 lbs), HDPE (10 lbs)
Drum Height	Base of drum to bottom of dome – 36" (meets Fed. M.U.T.C.D. VI, Section 6F-5e.) Base of drum to top of dome – 39" / Base of drum to top of handle – 41 1/2"
Drum Diameter	18" minimum (meets Fed. M.U.T.C.D. Part VI, Section 6F-5e.)
Reflectivity	H.I. / E.G. / D.G.
Reflective Band Size	4" / 6"
Light Brackets	2 each
Flag Brackets	2 each

OPTIONAL BASE

	Molded rubber snap-on base	Drop over base (natural bio-degradable materials or molded rubber)	Drop over base (blow-molded polyethylene plastic, sand fillable)	Sand filled snap-on (LDPE/ HDPE)	Sand bag snap-on base (LDPE/ HDPE)
Base Weight	25, 30, 40 lbs	28 lbs	3 1/2 lbs (empty) to 40 lbs (filled)	4 to 40 lbs	2 1/2"
Base Height	2.8"	3.25"	3.5"	3.5"	3.5"
Base Diameter	24"	26"	26"	24"	24"
Base Color	Black	Natural/black	Black/ cad. orange	Cad. orange	Cad. orange

All specifications and descriptions are subject to change without notification.

Patent No. 5,722,788
Patent No. 6,019,542

Distributed by:

Bent Manufacturing Company, Inc.

17311 Nichols Street
Huntington Beach, CA 92647-5721
(714) 842-0600 • FAX (714) 842-2959
(888) 842-0600 • FAX (888) 842-2368
E-Mail: BMC@bentmfg.com
<http://www.bentmfg.com>