

TYPE I & II WAFFLE BOARD PLASTIC PANEL BARRICADES



BENT MANUFACTURING COMPANY

TYPE I & II WAFFLE BOARD PLASTIC PANEL BARRICADES

FEATURES:

- The first and finest NCHRP-350 approved steel leg and plastic panel barricades.
- High impact resistant, unique 'waffle' pattern optimizes board strength and rigidity.
- High density copolymer polyethylene material is capable of withstanding extremely variable environmental conditions.
- Provided with pre-molded bolt holes.
- Bolt hole faces have been 'squared' to accept standard carriage bolts.
- Sheeting side of panel has a smooth surface to allow easy application of reflective sheeting.
- All pre-sheeted panels are flame treated.
- One year manufacturer's guarantee against defects in materials and workmanship.
- All barricade components are completely interchangeable and sold as complete units or separate items (panels & legs).



All specifications and descriptions are subject to change without notification.

Material	High density copolymer polyethylene with UV inhibitors
Dimensions (Panel size)	6" x 24", 8" x 24", 12" x 24" Thickness: .500 (1/2 inch)
Tensile Strength (ASTM) D638-72	4000 PSI
Elongation 2" min % (ASTM) D638-72	600%
Flexural Modulus (ASTM) D690-71	240,000 PSI
Brittle Temperature	-180°F
Softening Temperature	+320°F
Panel Color	White
Reflective Sheeting	EG SEG Hi-DG

Barricade Legs	Painted/Galvanized
Leg Thickness	1 1/4" x 14 & 12 gauge
Leg Material	Steel angle iron or steel roll formed
Leg Length	45" standard 'Universal Fitting'
Board Hole Pattern on Ctrs	4,6,10 inch

Distributed by:

Bent Manufacturing Company, Inc.

17311 Nichols Street

Huntington Beach, CA 92647-5721

(714) 842-0600 • FAX (714) 842-2959

(888) 842-0600 • FAX (888) 842-2368

E-Mail: bentmfg@ix.netcom.com

<http://www.bentmfg.com>



Printed U.S.A. 12/20/00 - 2000