



UNIVERSAL PLASTIC BARRICADE




BENT MANUFACTURING COMPANY



UNIVERSAL PLASTIC BARRICADE

FEATURES:


- Latest technology in stress and impact absorption.
- Bent Mfg. exclusive waffle-board design on back.
- Recessed areas for sheeting.
- Unique recessed molded light mount brackets sized for standard bolts.
- Protective anti-skid/wear tabs on bottom of legs.
- Non-shifting stacking lugs.
- Capable of internal sand ballasting.
- Custom name molding.
- Barricade lays flat upon impact.
- Holds many sizes of signs.
- Resistant to extreme temperatures.
- Convenient molded carry-handle.



Unique recessed molded light mount brackets sized for standard bolts.



Sturdy, cross-member reinforced design with holes and slots for easy sign attachment.



Convenient molded carry-handle.

SPECIFICATIONS:

Barricade Type	Type I 8" x 24" 12" x 24"	Type II 12" x 24" or 8" x 24" (top) 8" x 24" (bottom)
Material	High density polyethylene	
Color	White, yellow, orange	
Weight	14 pounds minimum	
Sand Ballasting	Maximum of 30 pounds	
Reflective Sheeting	S.E.G. / ENG. Grade / High Intensity	
Temperature Range	Freeze stress crack: -188° / Heat softening temperature: 216°	
Height	45"	
Width	24"	
Thickness	2-1/4"	

All specifications and descriptions are subject to change without notification.

Patent No. 5,458,434

Distributed by:

Bent Manufacturing Company, Inc.

17311 Nichols Street
 Huntington Beach, CA 92647-5721
 (714) 842-0600 • FAX (714) 842-2959
 (888) 842-0600 • FAX (888) 842-2368
 E-Mail: BMC@bentmfg.com
<http://www.bentmfg.com>