

SUPERDOME DRUM



**For Snap-On Base
or Drop Over Base**



For Tire Ring Base

BENT MANUFACTURING COMPANY BDAA, INC.

SUPERDOME DRUM and BASE

FEATURES:

- Double (one on each side) flag mount holes with pre-molded stops for all-purpose flagging situations.
- Enlarged arch carry handle allows gloved workers easy, comfortable and secure grip.
- Ribbed dome top for increased target value and superior structural strength.
- High gravity molded rubber base hugs the road as if it were "glued down."
- Recessed reflective band tiers, maximum width 6". Accommodates USA M.U.T.C.D. 2" maximum spacing specifications.
- Two pre-molded light mounts are designed for standard size bolt and cup washers.
- Rounded dome top discourages any dangerous debris or rocks to collect on top of drum.
- Tested and certified to meet the crashworthy requirements of NCHRP-350.



SPECIFICATIONS:

Drum Materials	Low or high density polyethylene
Color	Cad. orange
Drum Weight	LDPE (12 lbs), HDPE (10 lbs)
Drum Height	Base of drum to bottom of dome – 36" (meets Fed. M.U.T.C.D. VI, Section 6F-5e.) Base of drum to top of dome – 39" / Base of drum to top of handle – 41½"
Drum Diameter	18" minimum (meets Fed. M.U.T.C.D. Part VI, Section 6F-5e.)
Reflectivity	H.I. / E.G. / D.G.
Reflective Band Size	4" / 6"
Light Brackets	2 each
Flag Brackets	2 each

OPTIONAL BASE

Base Material	Molded rubber snap-on base	Drop over base (natural bio-degradable materials or molded rubber)	Drop over base (blow-molded polyethylene plastic, sand fillable)	Sand filled snap-on (LDPE/HDPE)	Tire Ring Ballast (Fits TR Drum)
Base Weight	25, 30, 40 lbs	28 lbs	3½ lbs (empty) to 40 lbs (filled)	4 to 40 lbs	22 to 26 lbs
Base Height	2.8"	3.25"	3.5"	3.5"	2" Average
Base Diameter	24"	26"	26"	24"	26"
Base Color	Black	Natural/black	Black/cad. orange	Cad. orange	Black Recycled Tire

All specifications and descriptions are subject to change without notification.

Patent No. 5,722,788
Patent No. 6,019,542

Bent Manufacturing Company

15442 Chemical Lane
Huntington Beach, CA 92649
(714) 842-0600 • FAX (714) 842-2959
(888) 842-0600
E-Mail: BMC@bentmfg.com
<http://www.bentmfg.com>

Distributed by: